

5 Sliding Door Latch Assembly

Cross-Reference to Related Applications

This application claims the benefit of United States Provisional application

10 Serial No. 60/214,493, filed June 27, 2000.

Statement Regarding Federally Sponsored Research or Development

Not Applicable

15

Reference to a Microfiche Appendix

Not Applicable

20 Background of the Invention

1. Field of the Invention

This invention relates to sliding door latch assemblies, and more particularly to the combination of a sliding door and latch assembly in which the latch, although behind or under the door pull handle, is conveniently operated by having the lever that operates the latch mounted beyond the area of the handle, and coupled to the latch by an elongated mechanism that translates the rotary action of the lever to rotary shifting of the latch from beyond the handle area.

25

2. Description of the Related Art

Sliding doors have leading stiles that fit to the doorjamb. The door lock comprises a latch that interfits with a keeper in the doorjamb. Sliding doors are heavy and may not slide easily after a time. Typical handles provide for but a finger hold to move the door. Accordingly, better, larger handles are required, but

30

there is little space on the latch assembly for the handle unless the area over the latch actuation mechanism is used. This handle placement, however, leads to difficulties in operating the mechanism in its hidden and difficult to reach location.

## 5 Brief Summary of the Invention

It is an object of the invention to enable the use in sliding doors of larger handles that can be gripped by more than the fingertips while avoiding the difficulties that such placement of the handle causes when the handle in order to be adequate in size and shape tends to block the hand movement needed to reach the latch and latch lever. It is a further object to eliminate the resultant interference with latch operation and door locking and unlocking that use of larger handles has precipitated.

It is another object of the invention to provide a sliding door and latch assembly that provides a large handle for door shifting but is readily latched as well. It is a further object to provide an improved latch assembly that is accessible despite the presence of the larger handle. It is a still further object to provide a sliding door latch assembly that vertically spaces the latch and the latch lever such that the lever is accessible beyond the handle while the latch is within the housing locus where the handle is located. It is a further and specific object to provide an elongated, vertically disposed 4-bar coupling of the spaced latch and lever that translates the rotation of the lever into rotation of the latch for shifting the latch into or out of latching relation with the latch keeper.





Fig. 1 is an exploded view of the invention sliding door latch assembly, partly broken away to show underlying parts;

Fig. 2A is a top plan view of the latch assembly;

Fig. 2B is a side elevation view thereof; and

5 Fig. 2C is a bottom plan view thereof.

### Detailed Description of the Invention

With reference now to the drawings in detail, in Figs 1 and 2 the invention  
10 sliding door latch assembly, generally indicated at 10, comprises a vertically  
extended housing 12 that is suitably a portion of the leading stile 14 of the sliding  
door 16. Housing 12 has a vertically disposed pull handle 18 opposite a housing  
locus 22 extending over a major portion of but not all of the vertical extent of the  
housing. The latch 24 proper extends from latch housing 25 that is mounted  
15 within the housing locus 22, the latch being is shiftable to and from the housing  
for locking the sliding door to a cooperating keeper 26 mounted in a sliding door  
jamb opposite the latch.

20 The latch 24 is suitably hook-shaped; its cooperating keeper 26 comprises  
a slot 27 sized to receive and retain the latch hook portion. Housing 12 is suitably  
rectangular in transverse cross-section and comprises front wall 28, rear wall 32,  
and side walls 34, 36. Housing front wall 28 is slotted to pass the latch 24 in  
shifting relation to and from the keeper 26. Side walls 34, 36 support the latch  
housing 25 10 in position through mounting screws 38. Pull handle 18 defines the  
door inside handle and is sized for encirclement by and grasping with several

fingers. An outside handle 42 is also fixed to the housing 12 to complete the door and latch assembly.

It will be noted that the handle 18 covers much of the housing locus 22, and will cover a latch-operating lever that is in the typical position. The invention places the latch 24 in the typical position in housing locus 22, but moves the latch operating lever to a position that is not behind or covered over by the handle 18. For this purpose the invention uses a 4-bar linkage that transmits the rotary motion of the lever to the latch actuator as follows: A rotary actuator 44 located within the housing locus 22 serves to shift the latch 24 in locking and unlocking relation by rotation of shaft 45 in latch housing a lot 47. A hand-operated lever 46 is rotatably mounted to the housing 12 beyond the housing locus 22. Lever 46 is vertically spaced a predetermined distance D from the rotary actuator 44 and rigidly linked to the rotary actuator for rotatably actuating the latch 24 by the rotatable lever without having the lever within the housing locus 22. Thus, hand actuation of the lever 46 and shifting of the latch 24 is free of interference from the pull handle 18.

Lever 46 includes a rotatable lever plate 48, the lever plate and the lever being mounted to a common pivot, shaft 52, for rotation together responsive to hand operation of the lever. The rotary actuator 44 comprises a rotatable latch plate 54, the latch plate and the latch being mounted to a common pivot, shaft 45, for rotation together responsive to actuation of the latch plate by the lever 46 and its rotatable lever plate 48 through the coupling of the plates 48 and 54 by a pair of bars 58, 62 movably fixed to either edge of the lever and latch plates and

all

10